GOODWE

Cutting-edge hybrid inverter with smart operation modes and powerful back-up capabilities

- Lower energy cost
- Smart and flexible solutions
- Uninterrupted power supply
- Superb safety and performance

The ET G2 hybrid inverter is designed to maximise energy output, enhance self-consumption, and facilitate extensive back-up power for homeowners. With power rating up to 15kW, intelligent load controls and a wide battery voltage range, the inverter caters to individual needs. To secure a high level of energy autonomy, combine the hybrid inverter with GoodWe HV battery, and connect the system to the GoodWe EV chargers and/or any smart-grid ready household appliances. By combining a variety of smart operation modes, the system can be optimized to further drive down energy cost.



- Smart operation modes
- Powerful backup
- Integrated smart meter

ET G2 Series Hybrid Inverter I 6 – 15kW I Up to 3 MPPTs I Three Phase I HV **EMEA**

ET G2 Series

GOODWE

Technical Data	GW6000-ET-20	GW8000-ET-20	GW10K-ET-20	GW12K-ET-20	GW15K-ET-20
Battery Input Data					
Battery Type			Li-Ion		
Nominal Battery Voltage (V)			500		
Battery Voltage Range (V)			150 ~ 720		
Start-up Voltage (V)			150		
Number of Battery Input			1		
Max. Continuous Charging Current (A)	30	30	40	40	40
Max. Continuous Discharging Current (A)	30	30	40	40	40
Max. Charging Power (W)	9000	12000	15000	18000	24000
Max. Discharging Power (W)	6600	8800	11000	13200	16500
PV String Input Data					
Max. Input Power (W)*1	9600	12800	16000	19200	24000
Max. Input Voltage (V)*2			1000		
MPPT Operating Voltage Range (V)			120 ~ 850		
Start-up Voltage (V)			150		
Nominal Input Voltage (V)			620		
Max. Input Current per MPPT (A)			16		
Max. Short Circuit Current per MPPT (A)			24		
Number of MPP Trackers	2	2	3	3	3
Number of Strings per MPPT			1		
AC Output Data (On-grid)					
Nominal Output Power (W)	6000	8000	10000	12000	15000
Nominal Apparent Power Output to Utility Grid (VA)	6000	8000	10000	12000	15000
Max. Apparent Power Output to Utility Grid (VA)*3	6000	8000	10000	12000	15000
Max. Apparent Power from Utility Grid (VA)	12000	16000	20000	20000	20000
Nominal Output Voltage (V)			400 / 380, 3L / N / PE		
Output Voltage Range (V)*4			170 ~ 290		
Nominal AC Grid Frequency (Hz)			50 / 60		
AC Grid Frequency Range (Hz)			45 ~ 65		
Max. AC Current Output to Utility Grid (A)*5	8.7	11.6	14.5	17.4	21.7
Max. AC Current From Utility Grid (A)	15.7	21.0	26.1	26.1	26.1
Power Factor			0.8 leading~0.8 lagging		
Max. Total Harmonic Distortion			<3%		
AC Output Data (Back-up)					
Back-up Nominal Apparent Power (VA)	6000	8000	10000	12000	15000
Max. Output Apparent Power without Grid (VA)	6000 (12000 @60sec)*6	8000 (16000 @60sec)	10000 (18000 @60sec)	12000 (18000 @60sec)	15000 (18000 @60sec)
Max. Output Apparent Power with Grid (VA)	6000	8000	10000	12000	15000
Max. Output Current (A)	13.0 (17.4 @60sec)	17.4 (23.3 @60sec)	21.7 (26.1 @60sec)	21.7 (26.1 @60sec)	21.7 (26.1 @60sec)
Nominal Output Voltage (V)			400 / 380		
Nominal Output Frequency (Hz)			50 / 60		
Output THDv (@Linear Load)			<3%		
Efficiency					
Max. Efficiency	98.0%	98.0%	98.2%	98.2%	98.2%
European Efficiency	97.2%	97.2%	97.5%	97.5%	97.5%
Max. Battery to AC Efficiency	97.2%	97.5%	97.5%	97.5%	97.5%
MPPT Efficiency			99.5%		
Protection					
PV Insulation Resistance Detection			Integrated		
PV AFCI3.0			Optional		
Residual Current Monitoring			Integrated		
PV Reverse Polarity Protection			Integrated		
Battery Reverse Polarity Protection			Integrated		
Anti-islanding Protection			Integrated		
AC Overcurrent Protection			Integrated		
AC Short Circuit Protection			Integrated		
AC Overvoltage Protection			Integrated		
DC Switch			Integrated		
DC Surge Protection			Type II		
AC Surge Protection			Type II		
Remote Shutdown			Integrated		
General Data					
Operating Temperature Range (°C)			-35 ~ +60		
Relative Humidity			0 ~ 100%		
Max. Operating Altitude (m)			4000		
Cooling Method			Natural Convection		
User Interface			LED, WLAN + APP		
Communication with BMS			RS485, CAN		
Communication with Meter			RS485		
Communication with Portal			WiFi + LAN + Bluetooth		
Weight (kg)	23	23	25	25	25
Dimension (W × H × D mm)			496 × 460 × 221		
Noise Emission (dB)	<30	<30	<30	<45	<45
Topology			Non-isolated		
Self-consumption at Night (W)*7			<15		
Ingress Protection Rating			IP66		
Mounting Method			Wall Mounted		

*1: Max. Input Power, not continuous for 1.6*normal power.
*2: For 1000V system, Maximum operating voltage is 950V.
*3: According to the local grid regulation.
*4: Output Voltage Range: phase voltage.
*5: The Max. AC Current Output to on-grid load is 13A, 17.4A, 21.7A, 21.7A, 21.7A separately.
*6: Can be reached only if PV and battery power is enough.
*7: No Back-up Output.
*: Please visit GoodWe website for the latest certificates.

GoodWe-Single page-20241022-EN-EMEA-V1.1. Information may be subject to change without notice during product improving.

This datasheet provides information about products offered in the EMEA region.