SOLAX CLOUD MONITORING



Pocket Wi-Fi

Feature

- Quick installation with "Plug & Play" function
- IP 65 dust prevention water proofing designs
- Stable data transmission and good reliability
- Low profile and nice exterior

Product Name	Pocket Wi-fi
Model	Pocket Wifi 2.0
Supply Voltage	+3.3V
Frequency	2.400~2.472GHz
Antenna Gain	3dBi
Data upload intervals	5mins
Degree of protection	IP 65
Dimension	82*40*24.5mm
Net weight	34g

Product Name	Pocket LAN 2.0
Supply Voltage	+3.3 V
Data upload intervals	5min
Ethernet	10/100M
Net weight	54g
Dimension	123*29*42mm
Degree of protection	IP 65



Pocket Lan

Feature

- Quick installation with "Plug & Play" function
- IP 65 dust prevention water proofing design
- Stable data transmission and good reliability
- Eco-green and modern design



Pocket Wi-Fi Plus

Feature

- Quick installation with "Plug & Play" function
- IP 65 dust prevention water proofing designs
- Stable data transmission and good reliability
- Low profile and nice exterior
- Increase the external antenna, the signal is stronger

Product Name	Pocket Wi-Fi Plus
Supply Voltage	+3.3V
Frequency	2.400~2.472GHz
Antenna Gain	3dBi
Data upload intervals	5mins
Degree of protection	IP 65
Dimension	108*42*28.8mm
Net weight	34g

METER & CT



DDSU666

- Single-phase meter
- 80 A



DTSU666

- Three-phase meter
- 80 A



DDSU666-CT

- Single-phase meter
- 200 A
- With CT



DTSU666-CT

- Three-phase meter
- 200 A
- With CT



SDM230-Modbus

- Single-phase meter
- 100 A



SDM630M-CT V2

- Three-phase meter
- 200 /600 /1500 A
- With CT



ADAPTER BOX

Max. output voltage[V]	277
Max. output current[A]	5
Rated input voltage[V]	12
Degree of protection	IP65
Operating ambient temperature range [°C]	-25~60