FOX ESS

DATASHEET

EP12

HIGH VOLTAGE STORAGE BATTERY

The EP12 is a high-performance, scalable battery storage system. Its modular design allows for maximum flexibility, making it suitable for a broad range of storage applications.
Additional batteries can be installed in parallel allowing for a maximum storage capacity of 46.08kWh.



- Scalable to 46.08kWh
- 90% Depth of Discharge
- Floor or Wall Mounting
- Compact & Easy Installation
- IP65 Protection Level

HIGH VOLTAGE | **EASY INSTALLATION** | **HIGH EFFICIENCY** | **EXPANDABLE SYSTEM** | **90% DOD**

www.fox-ess.com

TECHNICAL SPECIFICATIONS

SYSTEM NAME	EP12
MODEL	**EP12 Plus**
ELECTRICAL CHARACTERISTICS	
Battery Type	LFP ($LiFePO_4$)
Nominal Energy [kWh]	11.52
Nominal Voltage [V]	384.0
Operating Voltage [V]	348.0 ~ 438.0
Max. Charge/Discharge Current [A]*1	30
Recommend Charge Current [A]	15
Peak Discharge Current [A]	65 @60s
Peak Charge Current [A]	36 @5s
Battery Pack Round-Trip Efficiency [%]	≥95
Depth of Discharge [%]	90
Communication	CAN
Display	LED*5
Scalability	Max. 4 Units in Parallel
OPERATING CONDITIONS	
Installation Location	Outdoor/ Indoor
Operating Temperature [°C]	Charge: 0 ~ 55, Discharge: -10 ~ 55
Operating Temperature [°C] (warm up function on, optional)	Charge: -25 ~ 55, Discharge: -25 ~ 55
Storage Temperature [°C]	-10 ~ 40
Cooling Method	Natural Convection
Humidity [%]	5 ~ 95 (No Condensation)
Altitude [m]	Max. 3,000
PROTECTION	
Fire Protection Function	YES
MECHANICAL CHARACTERISTICS	
Dimensions (W*H*D) [mm]	710*640*185
Weight [kg] (±5%)	98
Cell Net Weight [kg] (±5%)	70
CERTIFICATES	
Safety	IEC62619
EMC	EN IEC 61000-6-1/2/3/4
Transportation	UN38.3
Ingress Protection	IP65

*1 The current is affected by temperature, cell voltage and SOC.