GOODWE

Smart Meter

GoodWe's single-phase Smart Meter is an energy meter designed for real-time power monitoring, enabling load tracking and export power management. When combined with GoodWe's SEMS monitoring platform, it provides comprehensive insights into residential energy usage. Its compact and high-precision design simplifies installation and operation, offering accurate data and seamless compatibility with residential energy solutions.



- Plug and play installation
- Working altitude up to 3km
- Accuracy Class 1.0
- CTs included

Model			GMK110	GMK110D
Input	Grid		Single-phase	
	Voltage	Nominal Voltage-Line to N (Vac)	230	
		Voltage Range (Vac)	85 ~ 288	
		Nominal AC Grid Frequency (Hz)	50 / 60	
	Current	Current Transformer Ratio	120A: 40mA	
		Number of Current Transformers	1	2
Communication			RS485	
Communication Distance (m)			1000	
User interface			2 LED	
Accuracy	Voltage / Current		Class 1	
	Active Energy		Class 1	
	Reactive Energy		Class 2	
Power Consumption (W)			≤5	
Structural Parameters	Dimensions (W × H × D mm)		19 × 85 × 67	
	Weight (g)		50	
	Mounting		DIN rail	
Environment Parameters	Ingress Protection Rating		IP20	
	Operating Temperature Range (°C)		-30 ~ +60	
	Storage Temperature Range (°C)		-30 ~ +70	
	Relative Humidity (non-condensing)		0% ~ 95%	
	Max. Operating Altitude (m)		3000	

*: Please visit GoodWe website for the latest certificates.
*: All pictures shown are for reference only. Actual appearance may vary.

GoodWe-Single page-20231010-EN-V2.1. Information may be subject to change without notice during product improving.