Sigen Power Sensor

For SigenMicro only

- Perfectly matched for SigenMicro series
- Direct cloud connection, zero data loss
- 24/7 monitoring, real-time App access
- Standalone OTA, exportable logs for O&M
- Plug-and-play antenna for easy setup
- Built for extremes from -40 to +70°C





ENJOY GREEN ENERGY

Sigen Power Sensor

Sigen Sensor	SP-CT100-WI	TP-CT100-WI	Units
Power Supply			
Grid connection type	1P2W	3P3W/3P4W	
AC input voltage range	100 ~ 277	100 ~ 277 (L~N) 173 ~ 480 (L~L)	Vac
Nominal AC frequency	50/60		Hz
Max. operating current	100		A
Measurement Accuracy			
Voltage accuracy	0.5%		
Current accuracy	0.5% (4~100A), 1% (1~4A), 3% (0.06~1A)		
Power accuracy	1%		
Frequency accuracy	0.2%		
Communication			
Interface	WLAN / RS485		
RF band	2.4		GHz
RS485 band rate	9600		bps
RS485 protocol	Modbus RTU		
General Data			
Dimensions (W / H / D)	19 / 90 / 66		mm
Weight	0.1		kg
Storage temperature range	-40 ~ 85		°C
Operating temperature range	-40 ~ 70		°C
Relative humidity range	0% ~ 95%		
Ingress protection rating	IP20		
Installation method	DIN Rail 35 mm		
Standard Compliance			
Standard	IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6		

1. This product is only available in specific regions. Please contact Sigenergy or local distributors for details.

Disclaimer: The information in this file is provided on an "as is" basis. To the fullest extent permitted by law, Sigenergy Technology Co., Ltd. excludes all representations and warranties relating to this file and its contents or which is or may be provided by any affiliates or any other third party, including in relation to any inaccuracies or omissions in this file.

Version: 20260130