# HYD-14.9-30K-T1

14.9 / 15 / 20 / 25 / 29.9 / 30 kW

*Three-phase hybrid inverter*




## Simplicity

- Light weight and convenient transportation
- LCD and App for easy commissioning

## Safety

- IP66 protection rating
- DC SPD type I+II, AC SPD type II
- AI based AFCI protection

## Flexibility

- Multiple inverters in parallel connection
- Supports intelligent control of non critical loads

## Robustness

- Maximum 200% PV input, and 40A per MPPT
- Supports 100% unbalanced loads
- 150% overload capability for 10 seconds
- Integration of generators to extend backup duration

www.sofarsolar.com

© As of November 2025, SOFARSOLAR Co.,Ltd. The depiction of colors and shape of the product may differ from the original. SOFAR reserves the right to make changes or improvements to the products without prior notice. Ordering information is valid for specialist retailers. All brands or logos are trademarks or registered trademarks of their respective owners. All rights, technical modifications, and errors reserved.

| Model | HYD-14.9K-T1-A | HYD-15K-T1 | HYD-20K-T1 | HYD-25K-T1 | HYD-29.9K-T1-A-PLUS | HYD-30K-T1-PLUS |
|---|---|---|---|---|---|---|
| **PV Input** | | | | | | |
| Recommended Max. PV Power | 30 kWp | 30 kWp | 40 kWp | 50 kWp | 60 kWp | 60 kWp |
| Max. Input Voltage | 1000 Vd.c. | | | | | |
| Start-up Voltage[1] | 200 Vd.c. | | | | | |
| Rated Input Voltage | 600 Vd.c. | | | | | |
| MPP Voltage Range | 160-950 Vd.c. | | | | | |
| Number of MPPT | 3 | | | | | |
| Max. Number of Input Strings per MPPT | 2/2/2 | | | | | |
| Max. Input Current | 40/40/40 A | | | | | |
| Max. Isc | 50/50/50 A | | | | | |
| **Battery** | | | | | | |
| Voltage Range | 600-1000 Vd.c. | | | | | |
| Number of Battery Input Channels | 1 | | | | | |
| Max. Charging Power | 30 kW | | | | | |
| Max. Discharging Power | 14.9 kW | 15 kW | 20 kW | 25 kW | 29.9 kW | 30 kW |
| Max. Charging Current | 50 A | | | | | |
| Max. Discharging Current | 23.8 A | 24 A | 32 A | 40 A | 47.8 A | 50 A |
| Battery Type[2] | Lithium-ion | | | | | |
| BMS Communication | CAN | | | | | |
| **AC Backup** | | | | | | |
| Rated Output Voltage | 3N~+PE, 380/400/415 Va.c. | | | | | |
| Rated Output Frequency | 50/60 Hz | | | | | |
| Rated Output Power | 14.9 kW | 15 kW | 20 kW | 25 kW | 29.9 kW | 30 kW |
| Rated Output Current | 22.6/21.5/20.7 A | 22.8/21.7/20.9 A | 30.4/28.9/27.8 A | 38.0/36.1/34.8 A | 45.4/43.2/41.6 A | 45.6/43.3/41.7 A |
| Rated Apparent Power | 14.9 kVA | 15 kVA | 20 kVA | 25 kVA | 29.9 kVA | 30 kVA |
| Max. Apparent Power | 14.9 kVA | 16.5 kVA | 22 kVA | 27.5 kVA | 29.9 kVA | 33 kVA |
| Max. Output Current | 22.6/21.5/20.7 A | 25.1/23.8/23.0 A | 33.4/31.8/30.6 A | 41.8/39.7/38.3 A | 45.4/43.2/41.6 A | 50.0/47.6/45.9 A |
| Peak Output Apparent Power[3] | 1.5 times of rated power, 10s | | | | | |
| THDv(@ linear load) | < 3% | | | | | |
| Switching Time | 10 ms default | | | | | |
| Asymmetric load | Yes, Supports 100% three-phase unbalanced load | | | | | |
| **AC Smartload/Generator** | | | | | | |
| Rated Output Voltage | 3N~+PE, 380/400/415 Va.c. | | | | | |
| Rated Output Frequency | 50/60 Hz | | | | | |
| Rated Output Power | 14.9 kW | 15 kW | 20 kW | 25 kW | 29.9 kW | 30 kW |
| Rated Output Current | 22.6/21.5/20.7 A | 22.8/21.7/20.9 A | 30.4/28.9/27.8 A | 38.0/36.1/34.8 A | 45.4/43.2/41.6 A | 45.6/43.3/41.7 A |
| Rated Apparent Power | 14.9 kVA | 15 kVA | 20 kVA | 25 kVA | 29.9 kVA | 30 kVA |
| Max. Apparent Power | 14.9 kVA | 16.5 kVA | 22 kVA | 27.5 kVA | 29.9 kVA | 33 kVA |
| Max. Output Current | 22.6/21.5/20.7 A | 25.1/23.8/23.0 A | 33.4/31.8/30.6 A | 41.8/39.7/38.3 A | 45.4/43.2/41.6 A | 50.0/47.6/45.9 A |
| **AC Grid** | | | | | | |
| Rated Voltage | 3(N)~+PE, 380/400/415 Va.c. | | | | | |
| Rated Frequency | 50/60 Hz | | | | | |
| Rated Output Power | 14.9 kW | 15 kW | 20 kW | 25 kW | 29.9 kW | 30 kW |
| Rated Output Current | 22.6/21.5/20.7 A | 22.8/21.7/20.9 A | 30.4/28.9/27.8 A | 38.0/36.1/34.8 A | 45.4/43.2/41.6 A | 45.6/43.3/41.7 A |
| Rated Apparent Power | 14.9 kVA | 15 kVA | 20 kVA | 25 kVA | 29.9 kVA | 30 kVA |
| Max. Apparent Power | 14.9 kVA | 16.5 kVA | 22 kVA | 27.5 kVA | 29.9 kVA | 33 kVA |
| Max. Output Current | 22.6/21.5/20.7 A | 25.1/23.8/23.0 A | 33.4/31.8/30.6 A | 41.8/39.7/38.3 A | 45.4/43.2/41.6 A | 50.0/47.6/45.9 A |
| Max. Input Current | 80 A | | | | | |
| THDi | < 3% | | | | | |
| Power Factor Range | 0.8 lagging - 0.8 leading | | | | | |
| **Efficiency** | | | | | | |
| Max. MPPT Efficiency | 99.9% | | | | | |
| Max. Efficiency | 98.0% | 98.0% | 98.2% | 98.2% | 98.2% | 98.2% |
| European Efficiency | 97.0% | 97.0% | 97.5% | 97.5% | 97.5% | 97.5% |
| Max. Efficiency of Charging/ Discharging[4] | 98.0% | 98.0% | 98.2% | 98.2% | 98.2% | 98.2% |
| **Protection** | | | | | | |
| DC Switch | Yes | | | | | |
| PV Reverse Connection Protection | Yes | | | | | |
| Battery Reverse Connection Protection | Yes | | | | | |
| Output Short Circuit Protection | Yes | | | | | |
| Output Overcurrent Protection | Yes | | | | | |
| Output Overvoltage Protection | Yes | | | | | |
| Insulation Impedance Detection | Yes | | | | | |
| Residual Current Detection | Yes | | | | | |
| Anti-island Protection | Yes | | | | | |
| Surge Protection[5] | PV: Type I+II, AC: Type II | | | | | |
| **General Parameter** | | | | | | |
| Inverter Topology | Non-Isolation | | | | | |
| Protective Class | Class I | | | | | |
| IP Rating | IP66 | | | | | |
| Overvoltage Category | AC III, DC II | | | | | |
| Operating Temperature Range | -30˚C ~ +60˚C (derating above + 45˚C) | | | | | |
| Relative Humidity Range | 5%-95% | | | | | |
| Max. Operating Altitude | 4000 m (derating above 2000 m) | | | | | |
| Standby Self-consumption[6] | <10 W | | | | | |
| Installation Method | Wall Mounted | | | | | |
| Dimensions (W×H×D) | 680×525×325 mm | | | | | |
| Cooling Mode | Intelligent Airflow | | | | | |
| Weight | 40 kg | | | | | |
| Communication | RS485, Optional: WiFi/4G/LAN | | | | | |
| Display | LCD & APP | | | | | |

[1] Minimum PV voltage to start MPPT operation. [2] Please refer to document "SOFAR inverter Model compatible battery list". [3] Full sun.
[4] Battery-AC maximum efficiency of battery charge and discharge. [5] According to EN/IEC 61643-11. [6] Standby loss at rated input voltage.

*All specifications are subject to change without notice.