SolarEdge Home Backup Interface

Three Phase, for Europe

BI-EU3P

BACKUP



Flexible Backup Interface

- Automatically provides backup power to home loads in the event of grid interruption
- Flexibility in which loads to back up – the entire home or selected loads
- Scalable solution to support higher power & higher capacity
- Seamless integration with the SolarEdge Home Hub Inverter to manage and monitor both PV generation and energy storage

SolarEdge Home Backup Interface

Three Phase, for Europe

BI-EU3P

	BI-EU3P(1)	UNITS
GRID CONNECTION		
AC Current Input	3 x 63	A
AC Voltage Line – Neutral (Min / Nom / Max)	184 / 230 / 264	V
AC Frequency Range	50 / 60	Hz
On Grid to Off Grid Switchover Time	< 3	Sec
OUTPUT TO DISTRIBUTION PANEL		
Maximum AC Current Output	3 x 63	A
AC Voltage Line – Neutral (Min/Nom/Max)	184 / 230 / 264	V
AC Frequency Range	50 / 60	Hz
Overvoltage Category	III	
ADDITIONAL FEATURES		
Supported Grid Topologies	TT, TN-S, TN-C-S(2)	
Operation During Backup	Disconnection of 3 phases + N from external grid; PE to Neutral connection on load side / disconnection configuration option on internal grid	
Number of Communication Inputs	1	
Communication	RS485	
Energy Meter (for Import/Export)	Integrated, 1.25% accuracy	
Manual Control Over Microgrid Interconnection Device	Yes	
STANDARD COMPLIANCE		
Safety	IEC/EN 62109-1	
Emissions	IEC 61000-6-2, IEC 61000-6-3, IEC 61000-3-11, IEC 61000-3-12, EN 55011	
INSTALLATION SPECIFICATIONS		
Supported Inverters	SolarEdge Home Hub Inverter – Single Phase SolarEdge Home Hub Inverter – Three Phase SolarEdge Nexis Inverter 1ph SolarEdge Nexis Inverter 3ph	
Grid / Loads Conductor Cross Section	6 – 25	mm^2
Grid / Loads Conduit Diameter	14 – 22	mm
Communication Cable Cross Section	0.2 – 1.5	mm^2
Communication Gland Diameter	5 – 15	mm
Weight	< 5	kg
Noise	< 50	dBA
Operating Temperature Range	-40 to +50	˚C
Relative Humidity Range	0 – 100	%
Protection Rating	IP65	
Dimensions (H x W x D)	390 x 238 x 147	mm
Environmental Category	Outdoor	
Pollution Degree	3	
Maximum Altitude Rating	2000	m

(1) Applicable for PN BI-NEUNU-3P-01 and BI-NEUNU-3P-02.
(2) For other topologies, contact SolarEdge support.

© SolarEdge Technologies, Ltd. All rights reserved. SOLAREDGE, the SolarEdge logo, OPTIMIZED BY SOLAREDGE are trademarks or registered trademarks of SolarEdge Technologies, Inc.
All other trademarks mentioned herein are trademarks of their respective owners. Date: May 13, 2026 DS-000142-EU. Subject to change without notice.

CE