COMMUNICATION

Antenna for Wi-Fi and ZigBee Wireless Communications

SE-ANT-ZBWIFI-KIT, SE-ANT-ZB-WIFI-03



Simple Wireless Connectivity

- Used to connect a SolarEdge device to the monitoring platform via Wi-Fi or ZigBee wireless communication
- Used to connect a SolarEdge device to Smart Energy devices via ZigBee communications
- Indoor or outdoor usage
- 5 years warranty
- Antenna external to inverter for wider range

/ Antenna for WiFi and ZigBee Wireless Communications

SE-ANT-ZBWIFI-KIT, SE-ANT-ZB-WIFI-03

Model number: AS4032-1

Compatible Inverters	SE-ANT-ZBWIFI-KIT	SE-ANT-ZB-WIFI-03	UNIT
	SExxx-xxxxxBxxx	SExxK-xxxIxxx4 (excluding SExxK-xxxPIxxxx)	
ELECTRICAL SPECIFICATIONS			
Frequency Range	2.4-2.5		GHz
Gain (Max)	5		dBi
Beam Width – Horizontal	360		Degrees
Beam Width – Vertical	30		Degrees
Maximum Input Power	5		W
VSWR	2.1:1		
Polarization	Linear		
Impedance	50		Ohm
Radiation	Omni Directional		
Antenna Type	Co-linear Dipole		
Antenna Design	Dipole Array		
Application	Indoor / Outdoor		
ENVIRONMENTAL SPECIFICATIONS			
Operating/Storage Temperature	-40 to +185 / -40 to +85		°F/ °C
Storage Humidity	10% to 90% non-condensing		
Operating Humidity	5% to 90% non-condensing		
MECHANICAL SPECIFICATIONS			
Dimension (Height x Diameter)	7.9 x 0.8 / 200 x 20		In / mm
Weight	0.11 / 50		lbs / g
Cable	RG316		
Cable length (Max)	53 / 135	70.9 / 180	In / cm
Connector	RP SMA	RP SMA + Right Angle Adapter	
Internal Material	PCB + spring		
Base Material	PC Lexan 503R-WH5151L or WH8G952 Sabic		
Number of devices in a box	5	1	

© SolarEdge Technologies Ltd. All rights reserved. SOLAREDGE, the SolarEdge logo, OPTIMIZED BY SOLAREDGE are trademarks or registered trademarks of SolarEdge Technologies, Inc.
All other trademarks mentioned herein are trademarks of their respective owners. Date: 05/2021 DS-000035-1.2-ENG. Subject to change without notice.

CE RoHS