SolarEdge Home

Short String Inverter

SE3K-RWB / SE4K-RWB / SE5K-RWB

INVERTERS



The ideal solution for small-scale residential PV systems

- Greater design flexibility by enabling significantly shorter strings for low power three phase PV systems
- Optimized for installations with complex roofs (multi-facets and different orientations)
- Supports optional smart energy devices and expansion of system capabilities
- Single vendor solution for seamless operation of all system components, and one address for warranty and service issues
- Seamless wireless connectivity with system devices such as SolarEdge Home Battery, via optional SolarEdge Home Network platform
- Excellent reliability with standard 12-year warranty (extendable to 20 or 25 years)
- Advanced safety features, including touch-safe DC voltage when the inverter is off or disconnected
- Quick inverter commissioning directly from the SetApp smartphone app
- Suitable for outdoor or indoor installations

SolarEdge Home Short String Inverter

SE3K-RWB / SE4K-RWB / SE5K-RWB

Applicable to inverters with part number	SE3K-RWBTEBEN4	SE4K-RWBTEBEN4	SE5K-RWBTEBEN4	Units
OUTPUT				
Rated AC Power Output	3000	4000	5000	VA
Maximum AC Power Output	3000	4000	5000	VA
AC Output Line Connections	3-phase, 4-wire / PE (L1-L2-L3-N), TN, TT			
AC Output Voltage – Line to Line / Line to Neutral (Nominal)	380/220; 400/230			Vac
AC Output Voltage – Line to Neutral Range	264.5			Vac
AC Frequency	50/60 ± 5 %			Hz
Maximum Continuous Output Current (per phase)	5	6.5	8	A
Grid Supported – Three Phase	3 / N / PE (WYE with Neutral)			
Utility Monitoring, Islanding Protection, Configurable Power Factor, Country Configurable Thresholds	Yes			
INPUT				
Maximum DC Power (Module STC)	4050	5400	6750	W
Transformer-less, Ungrounded	Yes			
Maximum Input Voltage	450			Vdc
Nominal DC Input Voltage	375			Vdc
Maximum Voltage to Earth	450			Vdc
Maximum Input Current	8.5	11.5	14	Adc
Reverse-Polarity Protection	Yes			
Ground-Fault Isolation Detection	350 kΩ sensitivity			
Maximum Inverter Efficiency	97.8			%
European Weighted Efficiency	94.6	95.7	96.3	%
Night-time Power Consumption	<4			W
ADDITIONAL FEATURES				
Supported Communication Interfaces(1)	2 x RS485, Ethernet, Wi-Fi(2), ZigBee for Smart Energy (optional), Cellular (optional)			
Inverter Commissioning	With the SetApp mobile application using built-in Wi-Fi station for local connection			
Smart Energy Management	Export Limitation, Home Energy Management (Device Control)			
STANDARD COMPLIANCE				
Safety	IEC-62109-1/2			
Grid Connection Standards	EN 50549-1			
Electromagnetic Compatibility (EMC)	EN/IEC 61000-6-1, EN/IEC 61000-6-2, EN/IEC 61000-6-3, EN/IEC 61000-6-4, EN 55011, FCC Part 15, EN/IEC 61000-3-2, EN/IEC 61000-3-3, EN/IEC 61000-3-11, EN/IEC 61000-3-12			
RoHS	Yes			
INSTALLATION SPECIFICATIONS				
AC Output	Cable gland diameter 15 – 21			mm
DC Input	2 x MC4 pair			
Dimensions (H x W x D)	540 x 315 x 260			mm
Weight	24.5			kg
Operating Temperature Range	-40 to +60(3)			°C
Cooling	Fan (user replaceable)			
Noise	< 50			dBA
Protection Rating	IP65 - outdoor and indoor			
Mounting	Brackets provided			
Number of Power Optimizers per String	8(4)/9 to 20			
Maximum Power per String	5625			W

(1) Refer to the Communications category in the Knowledge Center for specifications of optional communication options.
(2) Wi-Fi connectivity requires an external antenna.
(3) For power de-rating information refer to the Temperature Derating Technical Note.
(4) When using S500B/S650B/P404/P485/P505 power optimizers only, a minimum of eight power optimizers are required per string.

© SolarEdge Technologies, Ltd. All rights reserved. SOLAREDGE, the SolarEdge logo, OPTIMIZED BY SOLAREDGE are trademarks or registered trademarks of SolarEdge Technologies, Inc. All other trademarks mentioned herein are trademarks of their respective owners. Date: June 21, 2023 DS-000042-ENG. Subject to change without notice.

CE RoHS