INVERTERS

Three Phase Inverter with Synergy Technology

For Europe

SE50K / SE66.6K / SE90K / SE100K / SE120K



Powered by unique pre-commissioning process for rapid system installation

- Pre-commissioning feature for automated system validation and wiring during site installation and prior to grid connection
- Easy 2-person installation with lightweight, modular design (each inverter consists of two or three Synergy Units and one Synergy Manager)
- Independent operation of each Synergy Unit enables higher uptime and easy serviceability
- Built-in thermal sensors detect faulty wiring, ensuring enhanced protection and safety
- Designed to automatically reduce high DC voltage to touch-safe levels upon grid/inverter shutdown, with SafeDC™ and optional rapid shutdown
- Built-in arc fault protection
- Built-in PID mitigation for maximized system performance
- Monitored* and field-replaceable surge protection devices to better withstand surges caused by lightning or other events
- Streamlined cabling and lower BoS costs with single DC connection option
- Optional integrated DC safety switch eliminates the need for external DC isolators
- Built-in module-level monitoring with Ethernet or cellular communication for full system visibility

*Applicable only for DC and AC SPDs

/ Three Phase Inverter with Synergy Technology

For Europe

SE50K / SE66.6K / SE90K / SE100K / SE120K

Applicable to inverter with part number	SExxK-xxx0Ixxxx			SExxK- xxx8Ixxxx		
	SE50K[1] For 400V Grid	SE66.6K For 400V Grid	SE90K For 400V Grid	SE100K For 400V Grid	SE120K For 480V Grid	Units
OUTPUT						
Rated AC Active Output Power	50,000[2]	66,600[3]	90,000	100,000[4]	120,000[5]	W
Maximum AC Apparent Output Power	50,000[2]	66,600	90,000	100,000	120,000	VA
AC Output Voltage – Line to Line / Line to Neutral (Nominal)	380 / 220; 400 / 230				480 / 277	Vac
AC Output Voltage – Line to Line Range / Line to Neutral Range	304 – 437 / 176 – 253; 320 – 460 / 184 – 264.5				432 – 529 / 249 – 305	Vac
AC Frequency	50/60 ± 5%					Hz
Maximum Continuous Output Current (per Phase)	72.5	96.5	130.5[6]	145		Aac
AC Output Line Connections	3W + PE, 4W + PE					
Supported Grids	WYE: TN-C, TN-S, TN-C-S, TT, IT; Delta: IT					
Maximum Residual Current Injection[7]	200		300			mA
Utility Monitoring, Islanding Protection, Configurable Power Factor, Country Configurable Thresholds	Yes					
Total Harmonic Distortion	≤ 3					%
Power Factor Range	± 0.2 to 1					
INPUT						
Maximum DC Power (Module STC) Inverter / Synergy Unit	87,500 / 43,750	116,550 / 58,275	157,500 / 52,500	175,000 / 58,300	210,000 /70,000	W
Transformer-less, Ungrounded	Yes					
Maximum Input Voltage DC+ to DC-	1000					Vdc
Operating Voltage Range	680 – 1000					Vdc
Maximum Input Current	2 x 36.25	2 x 48.25	3 x 43.5	3 x 48.25	3 x 48.25	Adc
Reverse-Polarity Protection	Yes					
Ground-Fault Isolation Detection	167 kΩ sensitivity per Synergy Unit[8]					
Maximum Inverter Efficiency	98.3				98.1	%
European Weighted Efficiency	98					%
Nighttime Power Consumption	< 8		< 12			W
ADDITIONAL FEATURES						
Supported Communication Interfaces[9]	2 x RS485, Ethernet, Wi-Fi (optional), Cellular (optional)					
Smart Energy Management	Export limitation					
Inverter Commissioning	With the SetApp mobile application using built-in Wi-Fi access point for local connection					
Arc Fault Protection	Built-in, user configurable (according to UL 1699B)					
Rapid Shutdown	Optional (automatic upon AC Grid Disconnect)					
PID Rectifier	Nighttime, built-in					
RS485 Surge Protection (ports 1 + 2)	Type II, field replaceable, integrated					
DC Surge Protection	Type II, field replaceable, integrated					
AC Surge Protection	Type II, field replaceable, optional					
DC Fuses (Single Pole)	Optional, 25 A / 30 A					
DC Disconnect Switch	Optional					
Pre-Commissioning	Built-in[10]					
STANDARD COMPLIANCE						
Safety	IEC-62109-1, IEC-62109-2, AS3100					
Grid Connection Standards[11]	EN 50549-1, EN 50549-2, VDE-AR-N 4105, VDE-AR-N 4110, VDE V 0126-1-1, CEI 0-21, CEI 0-16, TOR Erzeuger Typ A+B, G99 Type A+B, G99 (NI) Type A+B, VFR 2019					
Emissions	IEC-61000-6-2, IEC-61000-6-3 Class A, IEC-61000-3-11, IEC-61000-3-12					
RoHS	Yes					

(1) Not available in all countries. For details about the supported inverters in your country, see Countries Supported by the SolarEdge Inverters.
(2) 49,990 in the UK.
(3) For sites under VDE-AR-N 4110, consider this as a 60 kW (at 90% Unom) inverter for site capacity calculations.
(4) For sites under VDE-AR-N 4110, consider this as a 90 kW (at 90% Unom) inverter for site capacity calculations.
(5) For sites under VDE-AR-N 4110, consider this as a 108 kW (at 90% Unom) inverter for site capacity calculations.
(6) For sites under VDE-AR-N 4110, the Maximum Continuous Output Current per Phase is 145 A.
(7) If an external RCD is required, its trip value must be ≥ 200 mA for SE50K/SE66.6K; ≥ 300 mA for SE90K, SE100K, SE120K.
(8) Where permitted by local regulations.
(9) For specifications of the optional communication options, visit the Communication page on the SolarEdge website or download the relevant product datasheet from the Knowledge Center.
(10) Not available for P/Ns SExxK-xxxxxBPxx.
(11) For all standards and certificates download, refer to the Certificates category in the Knowledge Center.

/ Three Phase Inverter with Synergy Technology

For Europe

SE50K / SE66.6K / SE90K / SE100K / SE120K

Applicable to inverter with part number	SExxK-xxx0Ixxxx			SExxK- xxx8Ixxxx		
	SE50K For 400V Grid	SE66.6K For 400V Grid	SE90K For 400V Grid	SE100K For 400V Grid	SE120K For 480V Grid	Units
INSTALLATION SPECIFICATIONS						
Number of Synergy Units per Inverter	2		3			
AC Wire Cross Section and Outer Diameter: Line/PE (Aluminum or Copper)	Cross section up to 120 / 70 mm^2; outer diameter 30-50 / 12-20 mm					
DC Input: Inverter / Synergy Unit(12)(13)	8 / 4 MC4 pairs		12 / 4 MC4 pairs			
	Gland, 2 pairs / 1 pair, cross section 25 – 70 mm^2, aluminum or copper Cable outer diameter 12 – 20 mm		Gland, 3 pairs / 1 pair, cross section 25 – 70 mm^2, aluminum or copper Cable outer diameter 12 – 20 mm			
Dimensions (H x W x D)	Synergy Unit: 558 x 328 x 273 Synergy Manager: 360 x 560 x 295					mm
Weight	Synergy Unit: 32 Synergy Manager: 18					kg
Operating Temperature Range	-40 to +60(14)					°C
Cooling	Fan (user replaceable)					
Noise	< 67					dBA
Protection Rating	IP65 – outdoor and indoor					
Mounting	Brackets provided					

(12) DC input is available with MC4 or Gland connection under the inverter part number. For more information, contact SolarEdge.
(13) OnlyMC4 connectors manufactured by Staubli are approved for use.
(14) For power de-rating information refer to the Temperature Derating technical note.

Accessories - SPDs (purchased separately)	
Accessory	**P/N**
AC SPD kit for Synergy Manager (5 units per box)	SE-AC-SPD-SM

SolarEdge is a global leader in smart energy technology. By leveraging world-class engineering capabilities and with a relentless focus on innovation, SolarEdge creates smart energy solutions that power our lives and drive future progress.

SolarEdge developed an intelligent inverter solution that changed the way power is harvested and managed in photovoltaic (PV) systems. The SolarEdge DC optimized inverter maximizes power generation while lowering the cost of energy produced by the PV system.

Continuing to advance smart energy, SolarEdge addresses a broad range of energy market segments through its PV, storage, EV charging, UPS, and grid services solutions.



SolarEdge
@SolarEdgePV
@SolarEdgePV
SolarEdgePV
SolarEdge
www.solaredge.com/corporate/contact

solaredge.com

© SolarEdge Technologies, Ltd. All rights reserved. SOLAREDGE, the SolarEdge logo, OPTIMIZED BY SOLAREDGE are trademarks or registered trademarks of SolarEdge Technologies, Inc. All other trademarks mentioned herein are trademarks of their respective owners. Date: January 30, 2024 DS-000008-EU Subject to change without notice.

Cautionary Note Regarding Market Data and Industry Forecasts: This brochure may contain market data and industry forecasts from certain third-party sources. This information is based on industry surveys and the preparer's expertise in the industry and there can be no assurance that any such market data is accurate or that any such industry forecasts will be achieved. Although we have not independently verified the accuracy of such market data and industry forecasts, we believe that the market data is reliable and that the industry forecasts are reasonable.

CE RoHS

solaredge