SH3.0/3.6/4.0/5.0/6.0RS

Residential Hybrid Single Phase Inverter



FLEXIBLE APPLICATION

- 80 V - 460 V wide battery voltage range
- Ideal for both retrofitting and new installations
- Built-in smart PID Zero function

ENERGY INDEPENDENCE

- Seamless transition to backup mode, for protection against power outages
- Fast Charging or discharging, enabling higher self-consumption results
- Built-in EMS with advanced customization


USER FRIENDLY SETUP

- Plug and play installation
- iSolarCloud monitoring available on App and Web
- Lightweight and compact, optimized for heat-dissipation


SMART MANAGEMENT

- Real time data (10 seconds refresh sample)
- 24/7 live online monitoring and with integrated display
- Online IV curve scan and diagnosis

CIRCUIT DIAGRAM



EFFICIENCY CURVE (SH6.0RS)



© 2024 Sungrow Power Supply Co., Ltd. All rights reserved. Subject to change without notice. Version 18

SUNGROW
Clean power for all

Type designation	SH3.0RS	SH3.6RS	SH4.0RS	SH5.0RS	SH6.0RS
Input (DC)					
Recommended max. PV input power *	4500 Wp	5400 Wp	6000 Wp	7500 Wp	9000 Wp
Max. PV input voltage **	600 V				
Min. PV input voltage / Startup input voltage	40 V / 50 V				
Rated PV input voltage	360 V				
MPPT operating voltage range ***	40 V – 560 V				
No. of independent MPP trackers	2				
No. of PV strings per MPPT	1 / 1				
Max. PV input current	32 A (16 A / 16 A)				
Max. DC short-circuit current	40 A (20 A / 20 A)				
Max. current for input connector	20 A				
Battery data					
Battery type	Li-ion battery				
Battery voltage range	80 V - 460 V				
Max. charge **** / discharge current ****	30 A / 30 A				
Max. charge / discharge power	6600 W				
Input / output (AC)					
Max. AC power from grid	10000 VA	10700 VA	11000 VA	12000 VA	13000 VA
Rated AC output power	3000 W	3680 W	4000 W	5000 W	6000 W
Max. AC output apparent power	3000 VA	3680 VA	4000 VA	5000 VA	6000 VA
Max. AC output current	13.7 A	16 A	18.2 A	22.8 A	27.3A
Rated AC voltage	220 V / 230 V / 240 V				
AC voltage range	154 V – 276 V				
Rated grid frequency	50 Hz / 60 Hz				
Grid frequency range	45 Hz – 55 Hz / 55 Hz – 65 Hz				
Harmonic (THD)	< 3 % (of rated power)				
Power factor at rated power / Adjustable power factor	>0.99 at default value at rated power				
Feed-in phases / connection phases	1 / 1				
Backup data （on grid mode）					
Max. output power for backup load *****	6000 W				
Max. output current for backup load ******	27.3 A				
Backup data （off-grid mode）					
Rated voltage	220 V / 230 V / 240 V (± 2 %)				
Rated frequency	50 Hz / 60 Hz (± 0.2 %)				
THDV(@Linear load)	< 2 %				
Backup switch time	< 10 ms				
Rated output power	3000W / 3000VA	3680W / 3680VA	4000 W / 4000 VA	5000W / 5000VA	6000W / 6000VA
Peak output power	8400 VA, 10s				
Efficiency					
Max. efficiency / European efficiency	97.4 % / 97.0 %	97.5 % / 97.1 %	97.6 % / 97.2 %	97.7% / 97.3%	97.7 % / 97.3 %
Protection & Function					
Grid monitoring	Yes				
DC reverse polarity protection	Yes				
AC short-circuit protection	Yes				
Leakage current protection	Yes				
DC switch(solar)	Yes				
Surge protection	DC Type II /AC Type II				
PID Zero	Yes				
Parallel operation on grid port / Max. No of inverters	Master-slave mode / 3				
Optimizer compatbility *******	Optional				
General data					
Topology (Solar / Battery)	Transformerless / Transformerless				
Degree of protection	IP65				
Dimensions (W * H * D)	490 mm * 340 mm * 170 mm				
Weight	18.5 kg				
Mounting method	Wall-mounting bracket				
Operating ambient temperature range	-25 ℃ - 60 ℃				
Allowable relative humidity range	0 % – 100 %				
Cooling method	Natural convection				
Max. operating altitude	4000 m				
Noise (typical)	< 45 dB (A)				
Display	LED digital display & LED indicator				
Communication	RS485 / Ethernet / WLAN / CAN				
DI / DO	DI * 4 / DO * 1 / DRM				
DC connection type	MC4 (PV, Max.6 mm²) / Evo2 Compatible (Battery, Max.6 mm²)				
AC connection type	Plug and Play (Grid Max.16mm², Backup Max.6mm²)				
Grid compliance	IEC/EN 62109-1, IEC/EN 62109-2, IEC 62116, IEC 61727, IEC/EN 61000-3-11, IEC/EN 61000-3-12, EN 62477-1, AS/NZS 4777.2:2020, EN 50549-1, CEI 0-21, G 98 / G 99, UNE 217002:2020, NTS V2 TypeA, C10/26				

* Max. input PV power is 13,000 Wp ** Input voltage exceeding the MPPT operating voltage range triggers inverter protection *** Please refer to the user manual for the full load MPPT voltage range **** Depending on the connected battery ***** Please refer to the user manual and modify the settings based on actual load power ****** Calculated based on 220V grid voltage ******* For optimizer compatibility, please consult Sungrow before placing an order

© 2024 Sungrow Power Supply Co., Ltd. All rights reserved. Subject to change without notice. Version 18