SUNGROW
Clean power for all

WiNet-S2

Wireless Communication Module

SMART AND FLEXIBLE

- Supporting DHCP, and automatic network transmission without configuration
- Applicable to scenarios in which wireless communication is inaccessible

SIMPLE AND EFFICIENT

- Support of local and remote parameter setting and firmware updates
- Support fast distribution network, automatic station building, and data interval in seconds
- Plug and play, quick installation

SAFE AND RELIABLE

- Password and encrypted transmission for data protection
- IP66, wide temperature range



Type designation	WiNet-S2
Basic data	
Supported device number	1
LED display	LED * 3
Communication	
Ethernet	10/100 Mbps self-adaption , Communcation distance ≤ 100 m
WLAN	2.4 GHz , 802.11 b/g/n
Power supply	
DC input	5 VDC , 2.1 A
Power consumption	Typ. 1.3 W
Ambient conditions	
Operating temperature	-30 °C ~ 60 °C
Allowable relative humidity range	≤ 95 % , non-condensing
Max. operating altitude	≤ 4000 m
Protection class	IP66
Mechanical parameters	
Dimensions (W*H*D)	48 * 132 * 36 mm
Installation	Plug and play

© 2023 Sungrow Power Supply Co., Ltd. All rights reserved. Subject to change without notice. Version 1